



temperature




humidity



CO₂



level




flow



position



Product overview



11/21



ADVANCED MEASURING
INSTRUMENTS

Official partner of SENSIT s.r.o.

HEAD TEMPERATURE SENSORS

- Type of sensing element:
 - Resistance – Pt 100/3850, Pt 500/3850, Pt 1000/3850, Ni 1000/5000, Ni 1000/6180, Ni 10000/5000, Ni 10000/6180, Ni 2226 = T1, Ni 891, NTC, PTC
 - Thermocouple – TCK, TCJ, TCT; Others – KTY, SMT 160, DALLAS, TSic etc.
- Maximum measuring range: -200 °C to 600 °C (custom manufactured sensors above the stated parameters)
- Ingress protection: up to IP 68 (according the sensor type)
- Output signal: resistance, current, voltage and digital
- Stem length: standardly 70 to 240 mm, custom manufactured from 40 mm to ... "according to customer's requirement"
- Stem material: stainless steel DIN 1.4301, DIN 1.4571, DIN 1.4404 and others "according to customer's requirement"
- Accessories: thermowells, welded-on pieces, reductions, brackets, flanges, clamps, connectors

↓ CONTACT (series S 140, S 150, S 190)



DIGI output

IoT application ready

↓ INTERIOR USE (series S 100)

DIGI output



↓ OUTDOOR USE (series S 110, K 110)



DIGI output

↓ IMMERSION (Ex) (series S 120, K 120, S 160, K 160, S 180, S MINI)

↓ HIGH TEMPERATURES (IP 68) (up to 600 °C)



DIGI output



DIGI output

↓ WITH CONNECTOR (TR 021, TR 021A, TR 021F, TR 02)

↓ WITH DISPLAY (series NSD)



TEMPERATURE PROBES

IP 68

- Design: contact, stick in, ambient temperature probe ■ up to 6 measuring points
- Maximum measuring range: -50 °C to 300 °C ■ Type of sensing element: Resistance: Pt 100/3850, Pt 500/3850, Pt 1000/3850, Ni 1000/5000, Ni 1000/6180, Ni 10000/5000, Ni 10000/6180, Ni 2226 = T1, NTC, Ni 891; Thermocouple: TCK, TCJ, TCT ■ Ingress protection: up to IP 68 (according to probe type)
- Case material: stainless steel DIN 1.4301 ■ Case diameter: from 1.5 mm... "according to customer's requirement"
- Handle material: silicone, teflon, polypropylene, LCP, PEEK ■ Cables: silicone, teflon, PVC



CABLE TEMPERATURE SENSORS

■ Type of sensing element:

Resistance - Pt 100/3850, Pt 500/3850, Pt 1000/3850, Ni 1000/5000, Ni 1000/6180, Ni 10000/5000, Ni 10000/6180, Ni 2226 = T1, Ni 891, NTC, PTC

Thermocouple - TCK, TCJ, TCT; Others - KTY, SMT 160, DALLAS, TSic etc.

■ Maximum measuring range: -200 °C to 450 °C (custom manufactured sensors above the stated parameters) ■ Connection: 2wire, 3wire, 4wire

■ Ingress protection: up to IP 68 (according the sensor type) ■ Case diameter: from 1,5 mm ..."according to customer's requirement"

■ Threads: standardly G 1/2", G 1/4", M 10 x 1, M 10 x 1,5 and others based on application ■ Cables: PVC, silicone, Teflon, fibreglass insulation and others

■ Case material: stainless steel DIN 1.4301, DIN 1.4571, DIN 1.4404, brass, dural and etc. ..."according to customer's requirement"

↓ SMOOTH CASE



↓ THREAD



↓ CONTACT



↓ BAYONETS



↓ PLASTIC CASE



↓ CRYOGENIC TEMPERATURE



↓ RIGHT-ANGLE



↓ ELECTROMOTOR WINDING



MINERAL INSULATED RESISTANCE TEMPERATURE SENSORS – MGO

■ Temperature range up to 600 °C ■ Case diameter from 1 mm ■ Type of sensing element: Pt 100, Pt 500 or Pt 1000 ■ Shapeable

↓ MINERAL INSULATED



↓ WITH CONNECTOR




↓ WITH CONNECTION HEAD



THERMOCOUPLE TEMPERATURE SENSORS

- Temperature range up to 1 200 °C
- Case diameter from 1 mm
- Types: TCK, TCJ, TCT, TCS etc.
- Shapeable

- ↓ MINERAL INSULATED
- ↓ WITH BAYONET
- ↓ WITH CONNECTOR
- ↓ WITH CONNECTION HEAD



PAIRED TEMPERATURE SENSORS

- Type of sensing element: Pt 100/3850, Pt 500/3850, Pt 1000/3850
- Compliance with standards: EN 60751, EN 1434; MID Certification
- Maximum temperature range: 0 °C to 180 °C
- Compatibility with measuring instruments of the following companies: SIEMENS, LADIS+GYR, KAMPSTRUP, ITRON, COMAC CAL, CODEA, SENSUS METERING and others
- Design variability: mounting into thermowell, direct immersion into the piping



BIMETALLIC TEMPERATURE SENSORS AND SWITCHES

Sensors

- Max. measuring range: -30 °C to 200 °C
- Measuring system: bimetallic
- Design: into thermowell, contact

Switches

- Switch off temperature from 70 to 180 °C
- Design: with a smooth stem, with a thread
- Contact design: normally open / normally closed



TEMPERATURE SWITCHES

- Design: on a DIN bar, on a console, for interiors and exteriors, for ducts, with an external probe, with or without a display, with an adjustable temperature/with a fixed temperature
- Input: Pt 100/3850, Pt 1000/3850, Ni 1000/6180, TCK
- Output: relay, RS 485
- Maximum measuring range: -50 °C to 600 °C
- Hysteresis: adjustable
- Power supply: 12/24 V or 230 V/50 Hz (according to the sensor type)



CUSTOM MADE

Complete service includes

- Thorough analysis of the application
- Production and delivery of samples
- Technical support and consulting design of sensor which you need, personal approach
- Price quotation is calculated on the base of required quantity
- Production of sensors including control of every sensor, for every piece
- Delivery date between 7 to 21 days
- Express production and delivery within possibilities of technological process



CONVERTERS

Temperature – Current / Temp. – Voltage / Temp. – RS 485 / Temp. – CAN protocol

- Output: 4 to 20 mA, 0 to 10 V, RS 485, CAN protocol ■ Power supply: 11 to 30 V_{DC} (according type)
- Standard measuring range: -30 °C to 60 °C, 0 °C to 35 °C, 0 °C to 100 °C, 0 °C to 150 °C, 0 °C to 200 °C, 0 °C to 400 °C; possibility of custom setting of the measuring range
- Design: on a DIN bar, wall-mounted version



DISPLAY UNITS

- Design: portable and panel units ■ Possibility of saving measured values
- Outputs: contact (2 x or 4 x relay), analogue (0 to 20 mA, 4 to 20 mA, 0 to 10 V)



TEMPERATURE AND RELATIVE HUMIDITY SENSORS

- Design: for interiors and exteriors, air-conditioning ducts, with an external probe
- Output: two galvanic separated signals 4 to 20 mA, 0 to 10 V, RS 485, CAN protocol
- Measuring range of relative humidity: 0 to 100 % RH ■ Maximum measuring temperature range: -30 °C to 125 °C according to the sensor type ■ "S" head design is in compliance with the temperature sensor, designed without mobile parts, high sensitivity ■ Option with display



TEMPERATURE, RELATIVE HUMIDITY AND CO₂ SENSORS

- Outputs: 4 to 20 mA, 0 to 10 V, RS 485, CAN protocol ■ Option with display
- LED identification ■ Design: for interiors and exteriors, air-conditioning ducts, with an external probe




COMBINED INTERIOR SENSORS

- Possible to choose a sensor version with various combinations of measured quantities (combination of two to five measured quantities) by selecting specific sensors ■ Outputs: RS 485, CAN protocol



FLOW SENSORS AND FLOW SWITCHES OF AIR AND LIQUIDS

- Design: for air-conditioning ducts ■ Liquid output: 4 to 20 mA, normally open contact
- Air output: voltage 0 to 10 V for sensors, 230 V / 8A relay for switches
- Recommended measuring range: 2 to 5 m/s, 2 to 10 m/s, 2 to 20 m/s
- "S" head design is in compliance with the temperature sensor, designed without mobile parts, high sensitivity



FLOOD DETECTORS

- Design: wall-mounted version or for horizontal surface, with external probe
- Output: the relay output or the output terminal of an open collector type ■ „S” head design



INDUCTIVE SWITCHES AND OPTICAL SENSORS

↓ INDUCTIVE PROXIMITY SWITCHES

Application:

- Rotation control ■ Press work presence
- Revolutions ■ Chain sag ■ Linear motion
- Products on a conveyor ■ Aperture
- Switch position ■ Material thickness
- Pressure ■ Door position ■ Rotary motion
- Object presence ■ Turbine revolutions
- Liquid level etc.



↓ OPTICAL LEVEL SENSORS

Suitable for:

- Food Processing Industry (dairies, production of alcoholic and non-alcoholic beverages, breweries)
- Chemical and Petrochemical industry
- Medical and Pharmaceutical industry



ACCESSORIES

- Thermowells, welded-on pieces, reducers, movable fittings, holders, connectors, bayonet adapters, thermal conductive paste...



Sensors for
Railway Vehicles

www.railwayvehicles.com

Sensors for Applications in
Rubber and Plastic Industries

www.sensit-rubberplastic.cz