## **KERN EW 4200-2NM**

The classic balance with robust tuning fork measuring system





Measuring system	
Adjustment options:	External calibration
Linearity:	20 mg
Minimum weight (USP):	20 g
Readability [d]:	10 mg
Recommended adjusting weight:	2 kg (E2); 2 kg (E2)
Repeatability:	10 mg
Resolution:	420000
Stabilisation time under laboratory conditions:	2 s
Warm up time:	4 h
Weighing capacity [Max]:	4,200 kg
Weighing units:	tl (Tw) ozt tl (HK) tol g mo lb tl (Singap. Malays) dwt ct oz

	ti (Singap. Malays) dwt ct oz
Display	
Display digit height (large):	1,700 cm
Technical data about verification	
Verification class:	II
Counting	
Counting resolution:	420000
Mininum piece weight at piece	10 mg

counting (Laboratory:

counting (Normal):

Mininum piece weight at piece

yes	
yes	
yes	
	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	30 °C
Minimum ambient temperature:	10 °C

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH
Operating time (Backlight off):	32 h
Operating time (Backlight on):	12 h
Rechargeable battery:	Rchrg, battery optional

Jei vice	
DAkkS Certificate:	963-127


Category	
Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & snipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	320 x 410 x 230 mm
Gross weight:	4,040 kg
Net weight:	2,862 kg
Shipping method:	Parcel service

Construction	
Casing material:	Plastic
Dimensions housing (WxDxH):	192 x 265 x 87 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (WxD):	180 x 160 mm

100 mg

## **KERN EW 4200-2NM**





## Piktogramme

STANDARD



**OPTION** 



**FACTORY** 

