

KERN 572-32

All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications



Functions

Conversion function:	yes
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Suspended weighing:	Loop
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

Power supply

Charging time:	10 h
Input voltage:	100 V - 240 V
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service

DAkkS Certificate:	963-127
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	3,800 kg
Net weight:	2,300 kg
Shipping method:	Parcel service

Construction

Casing material:	Cast aluminium alloys
Dimensions draft shield (ÅxH):	160 0
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	180 x 310 x 130 mm
Revolving screw feet:	yes
Weighing space (ÅxH):	157 43
Weighing surface (d):	105

Measuring system

Adjustment options:	External calibration
Linearity:	5 mg
Readability [d]:	1 mg
Recommended adjusting weight:	200 g (E2); 200 g (E2)
Repeatability:	2 mg
Resolution:	420000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	4 h
Weighing capacity [Max]:	420 g
Weighing system:	Strain gauge
Weighing units:	dwt ct oz tl (Tw) gn kg to t ozt tl (HK) g mo tl (Cn) lb tl (Singap. Malays)

Display

Display digit height (large):	1,800 cm
-------------------------------	----------

Counting

Counting resolution:	420000
Minimum piece weight at piece counting (Laboratory):	1 mg
Minimum piece weight at piece counting (Normal):	10 mg

KERN 572-32



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications

Piktogramme

STANDARD



OPTION

