KERN FXN10K-3N

Bench scale, protected by stainless steel and IP68 rating, now also with EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Linearity:	4 g
Number of weighing ranges:	1
Readability [d]:	2 g
Recommended adjusting weight:	15 kg (M1)
Repeatability:	2 g
Resolution:	7500
Stabilisation time under laboratory conditions:	2 s
Tare range:	-15 kg
Warm up time:	30 min
Weighing capacity [Max]:	15 kg
Weighing system:	Strain gauge
Weighing units:	oz kg g lb

	(A)
1115	

Display digit height (large): 2,500 cm

Counting		
Counting resolution:	7500	
Mininum piece weight at piece counting (Laboratory:	2 g	
Mininum piece weight at piece counting (Normal):	20 g	

Functions		
Counting function:	yes	
SLEEP function:	yes	
Weighing with tolerance range:	ves	

Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	25 %

Po		 	-	
$-\alpha$	M		Iه۱	ΙNΨ
	wv -	ub	IW	HBAY.

Battery: 4x1.5 V Size D
Operating time: 200 h

Service

Adjustment at the location of installation: 961-248

DAkkS Certificate: 963-128

Ca				
	P 1 7/4	AVA.	\sim	AW.
100	# II IL 4	719	ra i	

Brand: KERN
Category: Balances
Product Group: Bench scale

Packaging & shipping

Delivery: 24 h

Dimensions packaging (WxDxH): 325 x 365 x 225 mm

Gross weight: 3,800 kg

Net weight: 3,160 kg
Shipping method: Parcel service

Construction

Dimensions housing (WxDxH): 240 x 280 x 120 mm

Level indicator: yes

Material weighing plate: stainless steel

Overall dimensions mounted 240 x 280 x 120 mm

(WxDxH):

Revolving screw feet: yes

Weighing surface (WxD): 235 x 195 mm

Piktogramme

STANDARD















OPTION



FACTORY

