



More information on the website
radwag.com/en/info,w1,lJ5

WPT/4I 2000 S2 Livestock Scale



Functions



Plus/Minus Control



Percent Weighing



Totalizing



Parts counting



Internal battery



Peak hold



Newton unit measurement



Animal weighing

Datasheet

Metrological parameters	
Maximum capacity [Max]	2000 kg
Minimum load	20 kg
Readability [d]	1 kg
Tare range	-2000 kg
OIML Class	III
Physical parameters	
Display	LCD (backlit)
Weighing pan dimensions	1×2 m
Barriers height	1,8 m

Protection class	IP 67 construction, IP 68 (1h max)/69 indicator
Communication interface	
Communication interface	RS232
Electrical parameters	
Power supply	100 ÷ 240 V AC 50 / 60 Hz and battery
Operation time on batteries	45 h (average time)
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Relative humidity	10% ÷ 85% RH no condensation

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Receipt Printer
 RS 232 – Ethernet Converter
 Cigarette lighter receptacle power supply cables
 AP2-3 Current Loop Unit
 RS 232, RS 485 cables


Displays
 RS 232 cables (scale - EPSON printer)
 RS 232 cables (terminal - terminal)
 Stands, wall mounting kits and mounting brackets
 RS 232 – USB Converter

Software

RAD-KEY
 LabVIEW Driver

Scales Editor
 R-LAB

Device dimensions



Option of door customization
(opening direction and type due
to different combinations of hinges
assembling and various door models)

